

# STAINLESS STEEL PTZ-4200

## Internal cabling and telemetry receiver



All specifications and product descriptions are subject to changes without notice.

<b>Materials:</b>	Stainless steel AIS316
<b>Rotating Angle:</b>	Pan 0~350, Tilt -90~+60 (360 pan endless rotation:option)
<b>Rotating Speed:</b>	Pan 5°-12°/sec, Tilt 7°-12°/sec Max
<b>Wiper:</b>	Wiper standard
<b>Motor:</b>	DC24V/750mA
<b>Electric Power:</b>	Pan 25W, Tilt 25W
<b>Input Power:</b>	110V-240V 50/60Hz
<b>Temperature:</b>	-25°~+50°
<b>Weight:</b>	32kg
<b>Size:</b>	420Lx501Hx362W
<b>Address:</b>	255 Address (0-254)
<b>Interface:</b>	RS-485 Selectable by DIP switch between 2400 & 9600 BPS (Default 9600 BPS)
<b>Baudrate:</b>	8 Data, 1 stop, No parity
<b>Protocol:</b>	Pelco D

# STAINLESS STEEL PTZ-4200

## Internal cabling and telemetry receiver

**Built-in Camera: Samsung zoom camera SCZ-3430 43x**

**Key Features**

- High resolution of 600TV lines (Color), 700TV lines(B/W)
- Min. illumination 0.7Lux@F1.65 (Color), 0.07Lux (B/W)
- Powerful 43x zoom (3.2 ~ 138.5mm)
- WDR, VPS : True Day / Night (ICR)
- Intelligent video, MD, DNR (3D+2D)
- Composite video output
- Focus, AUTO

All specifications and product descriptions are subject to changes without notice.

