

RS-485 PAN AND TILT HEADS

PT-8001 Heavy Duty (Max Load 100/150 kg)



All specifications and product descriptions are subject to changes without notice.

Materials:

Color:

Motor

Rotate Angle:

Load Capacity:

Rotate Speed:

Input Power:

Temperature:

Weight:

Size:

Protection:

Electric power :

PT-8001/100 with AC motor:

Stainless steel/ Aluminum

Light gray

AC Motor 90W

Pan 0° to 350° ± 5°, tilt -45° to +45° ± 5°

100 kg:

Pan 6°/sec, Tilt 4.0°/sec (fixed Speed)

AC220V

-25° to +60°/ 90% (relative humidity)

65 Kg

421L×641H×366W

IP66

Pan 90W Tilt 90W

Built-in Receiver:

•Baud rate :

2400/4800/9600/19200 bps, N,8,1

•Protocol :

PELCO-D/P, Absolute position, Position readout

•Receiver function :

PRESETS: 100

AUX1,2,3,4,5 (Washer, IR, Wiper)

Control Motorized zoom lens (ZOOM, FOCUS) (extender control AUX6)

Built-in receiver address setting range from 0~up to 255

Communication interface : RS-485, RS-422

- Pan:
- Tilt:
- Load

PT-8001/100 AC motor

Fixed Speed 6°/sec

Fixed Speed 4°/sec

Capacity 100 kg

OPTIONAL

PT-8001/150 AC motor

- Pan:
- Tilt:
- Load

Fixed Speed 4°/sec

Fixed Speed 2°/sec

Capacity 150 kg

PT-8001/150 with AC motor:

Stainless steel/ Aluminum

Light gray

AC Motor 90W

Pan 0° to 350° ± 5°, tilt -45° to +45° ± 5°

150 kg:

Pan 4°/sec, Tilt 2.0°/sec (fixed Speed)

AC220V

-25° to +60°/ 90% (relative humidity)

65 Kg

421L×641H×366W

IP66

Pan 90W Tilt 90W